

220 S

Carry-deck crane with 22.000 kg capacity



FEATURES

MAX CAPACITY 22.000 kg
MAX BOOM EXTENSION 13,5 m
MAX BOOM ANGLE 75°
MINIMUM BOOM ANGLE 0°
WEIGHT 23.800 kg
CONFORMITY 2006/42 CE; 2014/30
CE; 2014/35 CE; 2000/14 CE; EN

CHASSIS 4 wheels, H shaped type structure made in high quality steel.

OPERATOR CABIN Ergonomic compliance, wide glass surface, FOPS compliance (ISO 13000).

WHEELS FRONT: n°2 super-elastic tyres 12.00 – R24" REAR: n°2 super-elastic tyres 12.00 – R24"

TRACTION Permanent all wheels drive system, with n°2 electric motor 30 kW 96V AC.

BRAKES Fully hydraulic, multi-disk type operating rear and front wheels, pedal control and hydraulic servo brake, automatic electronic brakes.

PARKING BRAKE S.A.H.R disc brakes in oil bath on both axles.

STEERING Double steering axles with three different configurations: front steering mode, crab steering mode, articulate steering mode.

LIGHTS Automotive headlamps and working light.

TURRET 360° slewing feature.

BOOM Manufactured in high quality steel manufactured, made by four elements: main boom and three synchronized hydraulic sections; hydraulic winch 22T.

TRACTION BATTERY | Armored plates 96 V 775 Ah. Battery charge indicator.


STABILIZATION 4 H-type outriggers installed on 4 indipendent H-type crossbars.

BOOM CONTROL | CAN-bus joystick.

DRIVE CONTROL Pedals and steering wheel.

SAFETY SYSTEM Electronic load moment indicator (LMI) with display for load, boom's position and boom's angle control.

Manual flying jib, radio remote control (for boom, turret, winch), InTouch system®, cabin air conditioning, self-lubricating system, bonding reel, airport lights, collision avoidance cameras, crossbars with three different areas available per side (0%, 50%, 100%), on board battery chargers.





Ergonomic operator cabin



Indipendent crossbars and outriggers



3T Manual Jib







CH-6405 Immensee (SZ) contact@schuler-schuler.ch Telefon +41 41 854 7000 Telefax +41 41 854 7001 www.schuler-schuler.ch